



The VISIONIS VIS-3026 is a mini case proximity reader with embedded design, compatible with any Wiegand input controller. The reader is fully potted and can function at extreme temperatures (-40°C ~ 60°C / -40°F ~ 140°F), which allows indoor and outdoor applications.

Features

- Metal case, anti-vandal
- Waterproof, conforms to IP66
- Wiegand 26~37 bits output (default: 26bits)
- Card type: EM card
- Reading range: Up to 7cm (2.8 inches)
- External LED control & external buzzer control

Modelo No.	VIS-3026
Operating Voltage	9~24V DC
Frequency	125KHz
Card Type	EM Card
Reading Distance	Up to 7cm (2.8 inches)
Output Format	Wiegand 26~37 bits
Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Standby Current	< 25mA
Index of Protection	IP66 (No ingress of dust; complete protection against contact (dust-tight). Protection against powerful water jets.)
Operating Humidity	10%~95% RH
Physical	Zinc-alloy Plate
Color	Silver & Black
Dimensions	L115 x W40 x H30 (mm) - L4.53 x W1.58 x H1.18 (in.)
Net Weight	105g



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com