



The VISIONIS VIS-3028 is a compact, waterproof stand-alone programmable access control Wiegand 26 card reader that provides proximity entry for up to 2000 users. It uses an Atmel microcontroller that assures maximum performance in any environment, and the low-power circuit makes its service life prolonged. The product has a simple design, easy operation, and high reliability.

## Features

- Metal case, embedded design, waterproof, conforms to IP66
- Read 125kHz EM card or tag
- One programmable relay operation, pulse mode, toggle mode
- Wiegand 26 bits output
- Wiegand 26/34 bits input automatic identification

Model No.	VIS-3028
Proximity Card Reader	EM
Radio Technology	125kHz Proximity Card
Read Range	0~6 cm (0~2.36 in.)
Wiring Connections	Relay output, exit button, Wiegand (in&out)
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
User Capacity	2000 Cards
Operating Voltage	12~24VDC
Idle Current	<50mA
Active Current	<150mA
Index of Protection	IP66 (No ingress of dust; complete protection against contact (dust-tight). Protection against powerful water jets.)
Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Operating Humidity	0%RH ~ 98%RH
Physical / Color	Stainless Steel Plate / Silver & Black
Dimensions	L115 x W70 x H25 (mm) - L4.53 x W2.76 x H0.98 (in.)
Unit Weight	230g



**Disclaimer:** VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com