



The VIS-600D-LED double door electric lock is for glass door, wooden door, fireproof door, sliding door and metal door. Inbuilt dry contacts lock status signal output (NO, NC, COM) and LED indicator to indicate the lock status.

Features

- Collinear load test 280kgx2, 600poundsx2.
- Dual voltage 12 or 24 VDC (optional).
- The standard voltage is 12VDC when finished.
- MOV provides reverse current protection.
- Anti-residual magnetism designed.
- High strength material, anodized aluminum housing.
- Design without mechanical failure.
- Increase the holding force, dual insulative housing.
- CE Certificate by European Union, MA Certificate by China Public Security Office.

Model No.	VIS-600D-LED
Size	500Lx48.5Wx25H (mm) - 19.67Lx1.90Wx0.98H (in.)
Armature Plate Dimension	180Lx38Wx11H (mm) - 7.09Lx1.50Wx0.43H (in.)
Holding Force	280kgx2 (600Lbsx2)
Input Voltage	12 or 24VDC
Current	12V/500mA*2 or 24V/250mA*2
Suitable	Wooden door, Glass door, Metal door, Fireproof door
Surface Temp.	≤+20°C (+68°F)
Operating Temp.	-10~+55°C (14-131°F)
Humidity	0~90% (non-condensing)
Cover Finish	Anodized aluminum
Lock Finish	Zinc
Armature Plate Finish	Zinc
Weight	4.2kg (9.26 pounds)



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com