



The VIS-DP105GD-FSA-LED is an all metal electric bolt lock. This device is built to last for a long time and can be used for doors with glass header frame and glass doors. It has an impressive 800kg/1700lbs of holding force. You can't get more secured than that.

Features

- Holding Strength: 800Kg (1700lbs)
- Function: Fail Safe (with power it's lock)
- Coil type: pure copper coil, ultra-low temperature continuous work
- Provides reverse current protection
- All metal mechanical structure, safe & durable
- Wide voltage DC12V-DC24V design for all security, building, fire power supply system
- With 10 sec door sensor detection function: the lock won't automatically open if remove the magnet plate after lock 10 sec

Model No.	VIS-DP105GD-FSA-LED
Voltage	DC12V - DC24V
Holding Force	800Kg (1700lbs)
Current	(DC12V): Working Current 110mA / Starting Current 1000mA
Function	Fail Safe. N/C with power it's lock
Time Delay	0/3/6 sec; Unlock time delay: 6 sec (If do not push the door after unlocking, again automatically lock)
Door Type	Suitable for fully frameless glass door (8~12mm thickness)
Size	Lock body: 145Lx44Wx38D (mm) - 5.70Lx1.73Wx1.50D (in.) Bracket: 145Lx44Wx26D (mm) - 5.70Lx1.73Wx1.02D (in.)
Product + Packaging Weight	0.93Kg (2.05 pounds)
Operating Temperature	-20°C / +50°C (-4°F / 122°F)
Cycles Tested	500.000



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com