



The Wireless PCB receiver has a 433MHz rolling code of encryption algorithm that guarantees higher-secure.

The programmable Wiegand output of the receiver makes it can work with most Wiegand controllers in the world.

### Features

- 433MHz rolling code technology
- Programmable Wiegand output of the receiver: 26 bits or 34 bits
- Communication distance: 30m maximum

Model No.	VIS-WPCB
Operating Voltage	12V DC
Working Current	≤15mA
Communication Frequency	433MHz
Communication Distance	30m Maximum
Wiegand Output Format	26 bits or 24 bits (Default is 26 bits)
Operating Temperature	-20°C ~+60°C (-4°F~+140°F)
Operating Humidity	0%~86%
Dimensions	L25 * W50 (mm) - L0.98 * W1.96 (in.)
Net Weight	10g



**Disclaimer:** VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com